SAFETY SUITE PLANT (SSP) BW ULTRA DEAKTIVACE MODULU BLUETOOTH

Floneywe

1. Přihlašte se do cloudové aplikace SSP.

2. Připojte detektor BW Ultra po mocí IR-Link adaptéru s kabelem.

Na obrázku vpravo vidíme displej detektoru BW Ultra se zapnutým modulem Bluetooth. To známená, že je možné se k detektoru připojit mobilním zařízením pomocí aplikace Honeywell Device Configurator.

SCZ



· (Honeywell Safety Suite X +				
	→ C ଲ 💲 sseu.honeywell.com/#/home/widgets				☆ 🧔 :
88	😌 Safety Suite GES CZ 🤤 https://sseu.honeyw 📙 Knowledge Base Ho 🙀 Portable Gas Detect 🙀 Gas Sensors Hone 🙀 Technical and Appli 侯	Mobile Application 💾 Requirem	nents to ins 🔟 Generátor čárových 💶 GES C	Z - detektory 🕌 Firmware Honeywell	Všechny záložky
	Honeywell Safety Suite Plant All Sites			4	⊻ © ? ŠS
88	Dashboard 12:52:30 PM, Mar 11 2025 Device Dashboard 🗸 🐲				Ø Edit
a	Past Events I Mar 03 2025 - Mar 09 2025 (By Date) ▲ O ALARMS(CRITICAL) ④ O ALERTS	Bump/Cal Forecast No Assigned Department, Mar 17 Double Department, Mar 17 Double Department, Mar 17	7 2025 - Mar 24 2025 S DUE	<u>1</u> (calibrati	.2 ; O ONS DUE
	In 19 10 12 12 12 14 15 16 17 18 19 20 21 22 23 24 5 6 7 8 9 10 11 12 13 14 16 16 17 18 19 20 21 22 23 24 O Total NO Assigned Department EVENT REPORTED ASSIGNED TO GAS READING DEPARTMENT SERIAL NUMBER TIME ELAPSED NO RESULT Image: Series and the series and t	Bump/Cal Status Today D 6 • DUE TODAY • N/A 0 408 • NOT DUE • UNIKNOW	WN BAMP OVERCE	156 • OL OVERDE • N	.* 1 1 ETODAY • N/A 241 15 STDUE • UNKNOWN
		414 Totat SERIAL NUMBER M KA420-1066953 G KA420-1067463 G KA420-10279 G	NODEL NAME : DEPARTMENT (BUND STATUS) BacklettMicz. • UNKNOWN IsaklettMicz. • UNKNOWN BacklettMicz. • UNKNOWN		TO \$
	*	KA424-0010286 G KA424-0007912 G	SasAlertMicr UNKNOWN SasAlertMicr UNKNOWN SasAlertMicr UNKNOWN		
	Top Events * : 122228 PM, Mar (Na 2025 - 122228 PM, Mar 11 2025	58128WF05244400213 8 58128WF05244400236 8 5220ULT01213900113 8 5220ULT01220200246 8 5220ULT01233200064 8	WYFFAX BUNKNOWN 3W-Flex BUNKNOWN 3W Ultra BUNKNOWN 3W Ultra BUNKNOWN		
		5812BWF05241800319 B	3W-Flex Ø UNKNOWN		*

3. V cloudové aplikaci SSP stiskneme ikonu správy zařízení vlevo nahoře.

4. Ujistíme se, že ve filtru u okénka vyhledávání máme zvolená pouze připojená zařízení ("DM Connected").

5. Po obnovení ("Refresh") a načtení detektoru do seznamu připojených zařízení klikneme na sériové číslo detektoru.

	Honeywell Safety Suite	× +									- a ×
÷	→ ଫ ଲ ∷ s	seu.honeywell.com/#/home/ec	uipment								☆ 🌀 :
88	😌 Safety Suite GES CZ	😌 https://sseu.honeyw 💾 K	nowledge Base Ho 🙌 F			e 📙 Technical and /	Appli 🔇 Mobile Application 📙	Requirements to ins 🔟 Generá	detektory 📙 Firmware He		Všechny záložky
=	Honeywell Sat	fety Suite Plant All Sites								t <mark>\$</mark>	⊚ @ ŠS
	Asset Management										+ ADD
	Device Docks	Template Locations									
-	Search for S/N	Ω	DM Connected								
2	1 Total								Export C Refresh	r∳i Import ∭	Manage Columns
â	🗌 🗞 DM 🗳										FIRMWARE VEF
				. A	Active DM I	BW Ultra		12:57:08 PM, Mar 11 2025			BRONF_01
											3
	G		5	C		7	. r.o .				

			a har in the second second	Contraction of the second
· 8	Honeywell Safety Suite × +			- a ×
← →	ට් බ සි sseu.honeywell.com/#/home/equipment/equipmentinfo?did=57054&dmO	nline=true&isRaeDevice=0&model=BW%20Ultra&status=2&subTitle=5220ULT01243600143&	tabIndex=4&title=BW%20Ultra	⊗ ☆ 💿 :
88	🛢 Safety Suite GES CZ 🤤 https://sseu.honeyw 👫 Knowledge Base Ho 🙌 Portable Gas Detect	👭 Gas Sensors Hone 🙌 Technical and Appli 📀 Mobile Application 💾 Requirements to in	is 🔟 Generátor čárových 💿 GES CZ - detektory 🕌 Firmware Honeywell	📔 🗅 Všechny záložky
= 1	oneywell Safety Suite Plant 🛛 All Sites 💛		4	± ⊚∣@ \$\$
	BW Ultra 5220ULT01243600143			
A	Detail Event Log Data Log Bump/Cal Results Settings Customize			
	GENERAL			
2	System			
٢	Startup Message	Operator ID	Lecation ID	
	Range: 0-50 characters BLE Paring PIN	Range: 1-8 characters	Range: 1~8 characters	
	····· Ø			
	Range: 6 characters			
	Instrument			
	Lockout on Self-Text Error	Sth Slot Sensor Installed	Flip Display	
	Latch Alarm Option	Enable Confidence Beep	Disable Button Power Off	
	STEL/TWA Backup	Steatth Mode	Hole Watch Mode	
		BLE Profile		
	BLE ENADIE	APP mode V		8
	Datalog			
	Demoteral Sizes Last	Log Interval (s)		
		13 Range: 1~120		
	IntelliFlash			
		IntelliFlash Interval (s)	IntelliFlash Mode	
	IntelliFlash	1	IntelliFlash Enabled 🗸	
		and the second and the second s	The second s	Contraction of the second

6. Pro vypnutí modulu Bluetooth přejdeme do záložky nastavení ("Settings") a odškrtneme políčko s názvem "BLE Enable".

7. Nastavení uložíme tlačítkem "Save" na konci stránky vpravo dole.

Ľ	Honeyweii sarety suite * +			
÷	→ O A Sseuhoneywell.com/#/home/equipment/equipmentinfo?did=57054&dmOnline=tr	rue&isRaeDevice=0&model=8W%20Ultra&status=2&subTitle=5220ULT01243600143&st	abindex=48ttitle=BW%20Ultra	* 🤨 :
88	😌 Safety Suite GES CZ 🤤 https://sseu.honeyw 📙 Knowledge Base Ho 🙀 Portable Gas Detect 👫 Ga	as Sensors Hone 📙 Technical and Appli 🧿 Mobile Application 📙 Requirements to ins.	🞦 Generátor čárových 😰 GES CZ - detektory 🕌 Firmware Honeywell 🛛 🛛 🗌	Všechny záložky
=	Honeywell Safety Suite Plant		\$ ⊻ ©	}∣@ <u>\$</u> \$
88	Policy Enforcement			
A				
	Forced on calibration	Forced on bump		
	Other Options			
â	Clear Peeks Type	iguage	50% LEL = (%CH4)	
	STEL/TWA + peaks V	inglish V	22 ~	
	Date & Time			
	Date & Time Time	Sync Now	Automatically adjust clock for DST	
Š.				
1.00	Show Time in 24-Hr Format			
	02			
	co			~
	H25			
	LEL			
	voc:			
2			CANCEL LOAD TEMPLATE	SAVE
	SESC	7		

Nyní se k detektoru BW Ultra nelze bezdrátově připojit!



Pro více informaci navštivte naše webové stránky www.detektory-plynu.cz



Zajímavá videa a videonávody naleznete na našem YouTube kanále www.youtube.com/@detektoryplynu



